



# MAGNETGLAZE PRO

## FITTING INSTRUCTIONS

Please read carefully before proceeding

Magnetglaze PRO is intended for internal use only and NOT recommended for use with glass. Magnetglaze PRO is particularly suitable for windows requiring quick or repeated removal. e.g. cleaning or ventilation purposes. Always fit your double glazing to the main window frame and not to the opening window. Make sure there is at least 19mm of flat mounting surface around each side of the window glass.

### TOOLS REQUIRED



Fine toothed saw



Tape Measure




Mitre Block



Pencil

### Using Magnetglaze PRO Step by Step

1. Remove the white metal strip from the length of Magnetglaze PRO.
2. Working with your plastic panel, measure the side to which you want to place a strip of Magnetglaze PRO. Add 3mm to this and squarely cut a length of Magnetglaze PRO to suit. Repeat for each side of the panel.
3. Using the outer corner as a reference (see diagram), insert the mitre bead and cut a 45° mitre using the fine toothed saw and mitre block. Repeat this step for all lengths.
4. Now fit the Magnetglaze PRO to the edges of the panel.
5. Hold the panel to the window frame so that it overlaps equally on each edge. Draw a pencil line round the panel on the frame
6. Cut and stick the white metal strip to the window frame, sticking it just inside the pencil marks.
7. Offer up the glazing panel to the window and "CLICK" - a perfect fit!



**For larger windows** we strongly recommend supporting the panel by placing a couple of screws, with the heads protruding 10mm or so, into the frame directly under the glazing panel. This will prevent the sheet from slipping down and becoming detached.

*It is always better to remove the glazing panel in summer to allow ventilation and prolong the useful life of the plastic.*